



Pro DN 10 až DN 150 se volí přivařovací přírubby s krkem pro PN 16.

DN	d ₁ DIN 2632	ČSN 131230	D	d	b	k	h ₁	d ₃	s	r	h ₂	d ₄	f	Šroubové otvory počet	d ₂	Hm. kg
200	219,1		340	-	24	295	62	235	5,9	10	16	268	3	8	22	11,3
		219		207				233	6							10,8
250	273		395	-	24	350	68	292	6,3	12	16	320	3	12	22	14,7
		273		260				288	6,5							10
300	323,9		445	-	26	400	68	344	7,1	12	16	370	4	12	22	17,4
		324		309				340	7,5							10
350	355,6		505	-	26	460	68	385	7,1	12	16	430	4	16	22	23,6
		377		359				394	9							10
400	406,4		565	-	28	515	72	440	7,1	12	16	482	4	16	26	28,6
		426		416				444	5							10
500	508		670	-	30	620	75	542	7,1	12	16	585	4	20	26	38,1
		530		520				550	5							12
600	610		780	-	34	725	80	642	7,1	12	18	685	5	20	30	44,6
		630		620				652	5							12
700	711		895	-	30	840	80	745	8	12	18	800	5	24	30	62,4
		720		708				6	12							18
800	813		1015	-	32	950	90	850	8	12	18	905	5	24	33	84,1
		820		806				7	12							18
1000	1016		1230	-	34	1160	95	1052	10	16	20	1110	5	28	36	115
		1020		1004				8	15	20						1110
1200	1220		1455	-	38	1380	115	1255	11	16	25	1330	5	32	39	182
		1220		1202				9	15	25		1325				5
1400	1420		1675	-	42	1590	120	1460	12	16	25	1535	5	36	42	248
		1420		1398				11	18	25		1525				5
1600	1620		1915	-	46	1820	130	1665	14	16	25	1760	5	40	48	347
		1620		1596				12	20	25		1750				5