



Pro DN 15 až 150 se volí zaslepovací přírubby pro PN 16.

| DN | D | b | k | d ₄ | f | d ₉ | šroubové otvory | | Hm. kg |
|-------|------|----|------|----------------|---|----------------|--------------------|----------------|-----------|
| | | | | | | | počet | d ₂ | |
| 200 | 340 | 24 | 295 | 268 | 3 | 197 | 8 | 22 | 15,7 |
| 250 | 395 | 24 | 350 | 320 | 3 | 247 | 12 | 22 | 21,7 |
| 300 | 445 | 26 | 400 | 370 | 4 | 297 | 12 | 22 | 30 |
| 350 | 505 | 26 | 460 | 430 | 4 | 347 | 16 | 22 | 38,7 |
| 400 | 565 | 28 | 515 | 482 | 4 | 396 | 16 | 26 | 52,2 |
| 500 | 670 | 30 | 620 | 585 | 4 | 496 | 20 | 26 | 78,6 |
| 600 | 780 | 34 | 725 | 685 | 5 | 594 | 20 | 30 | 122 |
| (700) | 895 | 36 | 840 | 800 | 5 | 692 | 24 | 30 | 172 |
| 800 | 1015 | 38 | 950 | 905 | 5 | 792 | 24 | 33 | 236 |
| 1000 | 1230 | 40 | 1160 | 1110 | 5 | 992 | 28 | 36 | 367 |
| 1200 | 1455 | 44 | 1380 | 1325 | 5 | 1192 | 32 | 39 | 575 |
| 1400 | 1675 | 50 | 1590 | 1525 | 5 | 1392 | 36 | 42 | 870 |
| 1600 | 1915 | 54 | 1820 | 1750 | 5 | 1590 | 40 | 48 | 1233 |