



Pro DN 10 až DN 150 se volí přivařovací příruby s krkem pro PN 16.

DN	d ₁ DIN 2632 ČSN 131230	D	d	b	k	h ₁	d ₃	s	r	h ₂	d ₄	f	šroubové otvory počet	d ₂	Hm. kg
200	219,1	340	-	24	295	62	235	5,9	10	16	268	3	8	22	11,3
	219		207				233	6							10,8
250	273	395	-	24	350	68	292	6,3	10	16	320	3	12	22	14,7
	273		260				288	6,5							10
300	323,9	445	-	26	400	68	344	7,1	10	16	370	4	12	22	17,4
	324		309				340	7,5							10
350	355,6	505	-	26	460	68	385	7,1	10	16	430	4	16	22	23,6
	377		359				394	9							10
400	406,4	565	-	26	515	72	440	7,1	10	16	482	4	16	26	28,6
	426		416				444	5							10
500	508	670	-	28	620	75	542	7,1	12	16	585	4	20	26	38,1
	530		520				550	5							12
600	610	780	-	28	725	80	642	7,1	12	18	685	5	20	30	44,6
	630		620				652	5							12
700	711	895	-	30	840	80	745	8	12	18	800	5	24	30	62,4
	720		708					6							12
800	813	1015	-	32	950	90	850	8	12	18	905	5	24	33	84,1
	820		806					7							12
1000	1016	1230	-	34	1160	95	1052	10	16	20	1110	5	28	36	115
	1020		1004					8	15						20
1200	1220	1455	-	38	1380	115	1255	11	16	25	1330	5	32	39	182
	1220		1202					9	15		25				1325
1400	1420	1675	-	42	1590	120	1460	12	16	25	1535	5	36	42	248
	1420		1398					11	18		25				1525
1600	1620	1915	-	46	1820	130	1665	14	16	25	1760	5	40	48	347
	1620		1596					12	20		25				1750